

*The Superior Air - Jacketed Hot Rubber Melters*  
(Propane, Diesel, & Electric Heat Systems Available)

From the Innovators of Rubber Master Technology

## A-40



This compact, liquid propane, under-fired melter has the same oil-less design as its larger brothers which reduces warm-up time to approximately 20 minutes. Extra high temperature insulation permits movement from one roof deck to another without burning the operator. The A-40's small dimensions allow it to fit into any elevator or through a standard doorway and the interchangeable power pack allows the contractor to purchase the super-quiet electric unit which is suited to a specific job where noise restrictions may be of concern.



Available with gas or electric drive

The Superior Air - Jacketed Hot Rubber Melters  
 (Propane, Diesel, & Electric Heat Systems Available)

From the Innovators of Rubber Master Technology

### A-40



#### SPECIFICATIONS: A-40 (35 US gallon capacity)

Heat Transfer Oil .....	None Required	Fire tube....	4" Sch 80 Stainless steel
Capacity (Custom Sizes Available) .....			35 US Gallons
Agitator .....	Honda 4.0 H.P. Gas, 110V Electric or Optional 6.0 HP Diesel Motor		
Overall Dimensions (Melter only) .....			L-62" W-31 3/4" H-47"
Burner.....	Adjustable Liquid Propane 1 X 300,000 BTU or Optional Beckett Diesel Burners		
Temperature Controls .....			Optional
Inner Shell .....			3/16" Rolled Steel
Outer Shell .....			1/8" Rolled Steel
Insulated Jacket .....	1/2 Super high temp plus 2" High Temp. Fiberglass		
Shipping Weight (Melter only) .....			800 lbs.
Optional Trailer (with melter mounted).....			L-11' x W-58" x H-66" 1,525 lbs.
Suspension 4" Drop Axle .....			3500 lb. Axle and Springs
Tires .....			2 X 6.00 X 14"
Trailer Chassis .....			4" Steel Channel
Brakes .....			Optional
Tow Hitch .....			As ordered c/w safety chain

#### Heated Material Output:

- material capacity: 35 US gallons
- heat up time: 30 min's (0.50 hr.)
- efficiency: 78.9% 35 gal. / .4hr. x 78.9% = 70 gal/ hr.