



A Hines Corporation Company

HatchProtector Roof Hatch Safety System



All Rooftop entry/exit points must be protected. The Garlock HatchProtector provides a non-penetrating affordable solution. With easy setup, HatchProtector can be used for both temporary and permanent solutions. The self-closing gate prevents accidental entrance.

The Garlock HatchProtector is designed to install quickly. The unique snap in place rails allow typical setup in 15 minutes or less with (2) persons.

HatchProtector mounts directly to the roof hatch with a compression fit design. No drilling necessary. means rooftop water integrity is not compromised. Multiple sizes are available to fit almost any hatch. Choose from either yellow powdercoated or galvanized coating for protection from the elements.

- Fast Installation
- Rugged design
- Compression Fit, NO DRILLING
- Self-closing gate
- Galvanized or yellow powdercoated
- Multiple sizes to choose from



www.profastinc.com

HatchProtector Roof Hatch Safety System



Self-closing Gate prevents accidental entry.



Unique compression fit design. No Drilling!



Width adjustable to allow for hatch size variations.



Rails simply snap together for quick, easy assembly.



Rugged hinges allow gate tension adjustment.



Rail pads protect roof surface.

SPECIFICATIONS



Penetrating

Top Rail Height = 42" Mid Rail height = 20" Multiple sizes Available:

- 30" x 36"
- 36" x 36"
- 30" x 54"
- 30" x 96"
- 36" x 54"
- 36" x 96"
- 42" x 42"
- 48" x 48" 48" × 60"

COMPLIANT

Available in yellow or galvanized.



Meets OSHA 1910.23(a) (8) and 1926.501(b) (4)

Philadelphia Office

6 Poulson Ave PROFAST P.O. Box 156 Essington, PA 19029 Phone: 610-521-3404

Fax: 610-521-4717

Harrisburg Office

7917 Derry St Suite 106 Harrisburg, PA 17111 Phone: 717-458-5610

Fax: 717-458-5613

Pittsburgh Office

503-5 North Drive Sewickley, PA 15143 Phone: 412-259-8449 Fax: 412-291-3188